客户 Customer: 日期 DATE:

纳入仕样书
SPECIFICATION

产 品 名 称 PRODUCT NAME: 声表滤波器

SAW Filter

贵 司 料 号 YOUR PART NO.:
敝 司 料 号 OUR PART NO.: MS11U2G45-W1H
版 本 号 VERSION.: V1.2

接受 RECEPTION THE SPECIFICATION HAS BEEN ACCEPTED. 该纳入仕样书已被我司接受 日期： DATE： 公司： COMPANY：		
批准 CFMD	审核 CHKD	接收 RCVD

深圳市麦捷微电子科技股份有限公司
SHENZHEN MICROGATE TECHNOLOGY CO.，LTD
TEL：86-755-28085000
FAX：86-755-28085605

CFMD. 批准	CHKD. 审核	DSGD. 担当
赵拥军	赖定权	赵新佳

纳入仕样书改定履历

MODIFY HISTORY OF SPECIFICATION

NO.	修改日期/DATE	修改内容/CONTENT	批准/APPROVED
1.0	2023.08.16	初稿 /New Released	赵拥军
1.1	2023.08.24	版本升级/Version Upgrade	赵拥军
1.2	2023.08.31	版本升级/Version Upgrade	赵拥军

目录 CATALOG

1 适用范围 Scope 4
2 品名构成 Product Identification 4
3 尺寸和管脚定义 Dimensions and PIN Configurations 4
4 推荐焊盘与测试电路 Recommended Land Pattern and Test Circuit 4
5 电气性能 Electrical Characteristics 5
6 包装 Packaging 8
7 装箱清单及标志 Packing documents and marking 9
8 保管 Storage 11

1 适用范围 Scope


麦捷声表滤波器系列产品设计用于 WIFI、GPS、移动电话和无绳电话机等相关市场中。
Microgate SAW Component is applicable for WIFI/GPS/Mobile phone/Cordless phone relevant market.

2 品名构成 Product Identification

MS	11	U	2G45	–	W	1	H
①	②	③	④		⑤	⑥	⑦

① 麦捷声表滤波器/Microgate SAW
② 尺寸/Size：11 (20-2016, 18-1814,15-1511,14-1411, 11-1109)
③ 输出/Output：U (B-Balance out, U-Unbalance out)
④ 频率/Frequency：2G45（2G45-2.45GHz)
⑤ 型号/Type：W (WLAN：Wireless Local Area Networks，无线局域网络)
⑥ 频段/Band：1 (1：ISM 2.4GHz 频段)
⑦ 流水号/Serial number


3 尺寸和管脚定义 Dimensions and PIN Configurations




PIN NO.	(1)	(2)	(3)	(4)	(5)
PIN Name	Input	GND	GND	Output	GND

4 推荐焊盘与测试电路 Recommended Land Pattern and Test Circuit

Land Pattern
Unit:mm



Test Circuit
Bottom View



5 电气性能 Electrical Characteristics

操作温度范围 Operating Temperature Range : -20 to +85℃

保存温度范围 Storage Temperature Range : -40 to +85℃

测试温度范围 Test Temperature: 25℃±2℃

湿度敏感等级 Moisture Sensitivity Level: MSL 2a

静电敏感等级 Electrostatic Discharge(ESD) Sensitivity: 250V (Human Body Model)

端口电压 D.C. Volatage between the terminals: 3V (25℃±2℃)

Table1. Electrical Specification


No.	Item	Frequency	Specification			
		(MHz)	Min	Typ.	Max	Unit
1	Insertion Loss	2403.1 ~ 2420.9		1.65 (1)	2.1 (1)	dB
2		2408.1 ~ 2425.6		1.45 (1)	1.8 (1)	dB
3		2413.1 ~ 2465.9		1.4 (1)	1.7 (1)	dB
4		2453.1 ~ 2470.9		1.45 (1)	1.7 (1)	dB
5		2458.1 ~ 2475.9		1.5 (1)	1.8 (1)	dB
6		2463.1 ~ 2480.9		1.7 (1)	2.1 (1)	dB
7	Ripple Deviation	2403.1 ~ 2480.9		1.2	2.0	dB
8	Absolute Attenuation	DC ~ 960	27	32		dB
9		960 ~1570	25	30		dB
10		1570~1580	25	30		dB
11		1580~1710	25	30		dB
12		1710~1910	25	30		dB
13		1910~1980	25	30		dB
14		2110~2170	26	31		dB
15		2640~3000	26	31		dB
16		3000~4800	25	30		dB
17		4800~5000	39	44		dB
18		5000~6000	31	36		dB
19	VSWR	2403.1 ~ 2480.9		1.8	2.2	
20	Input Signal Level	Max：28dBm				

（1）Averaged value within each Wifi channel width of 17.8 MHz .


Frequency Performance


Frequency Response






VSWR


Tr2 S11 SWR 1.000/ Ref 1.000 [F2]
10.00
9.000
8.000
7.000
6.000
5.000
4.000
3.000
2.000
1.000
0.000
2
1 Center 2.442 GHz
IFBW 70 kHz
Span 600 MHz
C?


Tr2 S22 SWR 1.000/ Ref 1.000 [F2]
10.00
9.000
8.000
7.000
6.000
5.000
4.000
3.000
2.000
1.000
0.000
2
1 Center 2.442 GHz
IFBW 70 kHz
Span 600 MHz
C?

6 包装 Packaging

① 编带尺寸 Dimensions of Tape:




Unit: mm

Ao	1.10	+/- 0.05
Bo	1.30	+/- 0.05
Ko	0.70	+/- 0.05
F	3.50	+/- 0.05
P1	4.00	+/- 0.10
W	8.00	+0.30/-0.10

② 带轮尺寸 Dimensions of Reel


Unit: mm




A	178±2
B	60±2
C	13.0±0.5
D	21.0±0.8
E	2.0±0.5
W	8.5±1.0
t	1.2±0.2
R	1.0±0.25

Reel material: PS (Polystyrene)


③ 编带简图及拉伸方向 Taping figure and drawing direction:





④ 盖带的剥离强度 Peeling strength of cover tape:

盖带 Cover tape	0.1~1.0N (10gf~100gf)



测试条件 Test condition:

1) 剥离角度 peel angle: 165°~180° vs. carrier tape.
2) 剥离速度 peel speed: 300mm/min±10%.

⑤ 包装数量 Packaging quantities: 5000 PCS / Reel

7 装箱清单及标志 Packing documents and marking

① 包装文件 Packing documents

a.装箱清单 Packing list.

b.合格证书 Certificate of compliance.


② 盘上标记 Marking on reels:

a. 麦捷料号 MICROGATE Part No.

b. 生产批号 Lot number

c. 盘装数量 Quantity per reel

d. 检验员号 Inspector No.



以上内容必须在标签上注明.All above shall be shown on marking label


麦捷公司标签如下所示：MICROGATE marking label will be as following:

MICROGATE


CUSTOMER:	P. O. NO	
CUSTOMER PART NO:	DATE CODE	LOT NO
MG PART NO:	QUANTITY	INSP. NO

MG PART NO

检验合格后，检验员在标签上盖上合格章。合格章如下所示：The eligible reels will be pressed a mark onto the surface. The mark will be as following:



③ 内包装盒标记:Marking on inner box



a.型号 MICROGATE part No.

b.每盒数量 Quantity per box

c. 包装日期 Date

以上内容必须在标签上注明（标签见 7.2 所示）。Above shall be shown on marking label (The marking label is shown in item 7.2).

④ 外包装箱标记 Marking on outer case:

1) 制造商 Manufacturer: “MICROGATE” ①

“中国深圳制造” “Made in Shenzhen CHINA”②

2) 发运标记 Ship marking:


“向上” “UP”, “小心轻放”“HAND CARE”, “防潮”“MOISTURE-PROOF”.

3) 包装标签包括以下内容 Packing label include the following:

a.型号 MICROGATE Part No

b.总数量 Total quantity per case

c.包装日期 Date;



以上内容必须在标签上注明。(参见 7.2 所示)

All above shall be shown on marking label. (The marking label is shown in item 7.2)

8 保管 Storage

保存条件 Storage conditions

●存放货物的库房应满足以下条件 Products should be storage in the warehouse on the following conditions

温度 Temperature: ≤40℃

湿度 Humidity : ≤70% relative humidity

不允许温、湿度有极剧变化。No rapid change on temperature and humidity

●禁止将产品保管在腐蚀性物质中，例如硫磺、氯气或者酸，否则将引起端头氧化，导致降低焊接性。Don't keep products in corrosive gases such as sulfur, chlorine gas or acid, or it may cause oxidization of electrode, resulting in poor solder ability.

●为了避免受潮气、灰尘等物质的影响，产品应保管于货架上。Products should be storage on the palette for the prevention of the influence from humidity, dust and so on.

●产品保管在库房中时，应避免热冲击，振动以及直接光照等等。Products should be storage in the warehouse without heat shock, vibration, and direct sunlight and so on.

●产品应密封包装 Products should be storage under the airtight packaged condition.