

RF Inductor



BWLD Series



Overview

Wire-wound RF inductors are electronic components designed to store energy in a magnetic field when electrical current passes through them. They are constructed by winding a conductive wire (usually copper or gold-plated) around a core material such as air, ceramic, or ferrite.

This configuration allows them to provide high inductance values with minimal power loss, especially at high frequencies.

Benefits

1. High Q-Factor (Quality Factor)
2. Low DC resistance design
3. High Current Handling
4. Can maintain excellent thermal stability at different temperatures

Applications

1. Industrial and Medical Equipmen: RFID systems and medical imaging equipment.
2. Data Centers
3. Networking
4. Base Station
5. Consumer Electronics
6. Security system

Product Information


Series	Size Code (JIS/EIA)	Inductance (nH)
BWLD	1608/0603 2012/0805 2520/1008	0.9 ~ 100



BWLD00241715 Series Specification

1 Scope: This specification applies to Wire Wound Ferrite Chip Inductors

2 Part Numbering:




3 Rating:

Operating Temperature: - 40°C ~ 105°C
(Including self - temperature rise)

Storage Temperature: - 40°C ~ 105°C
(The storage temperature range is for after the assembly)

4 Marking:




EX Marking: 1st → BLK

5 Standard Testing Condition

	Unless otherwise specified	In case of doubt
Temperature	Ordinary Temperature(15 to 35°C)	20 to 30°C
Humidity	Ordinary Humidity(25 to 85% RH)	50 to 80 %RH

BWLD00241715 Series Specification

6 Configuration and Dimensions and Unit Weight:



Dimensions in mm

TYPE	A	B	C	F	D	E	G	H	I	J
241715	2.25±0.15	1.57±0.15	1.37±0.15	0.5±0.1	0.7	1.0	1.27	1.78	1.02	0.95

Net Weight (grms)

SIZE CODE	Net Weight (grms)
241715	0.0107 (typ.)

7 Electrical Characteristics:

Part No.	Inductance (uH)	L/Q Test Freq. (MHz)	Q Typ.	SRF (MHz)Min.	RDC (Ω)±30%	IDC (mA)	Tolerance (±%)	Color Code 1st
BWLD002417151R0□00	1	7.96	18	100	0.1	800	10,20	BLK
BWLD002417151R5□00	1.5	7.96	18	90	0.18	650	10,20	BRN
BWLD002417152R2□00	2.2	7.96	18	70	0.24	550	10,20	RED
BWLD002417153R3□00	3.3	7.96	18	55	0.3	450	10,20	ORN
BWLD002417154R7□00	4.7	7.96	18	50	0.47	360	10,20	YEL
BWLD002417156R8□00	6.8	7.96	18	60	0.75	290	10,20	GRN
BWLD00241715100□00	10	2.52	18	25	0.9	290	10,20	BLU
BWLD00241715150□00	15	2.52	18	25	1.6	230	10,20	VIO
BWLD00241715220□00	22	2.52	18	17	1.95	190	10,20	GRY
BWLD00241715330□00	33	2.52	17	15	2.6	120	10,20	WHT
BWLD00241715470□00	47	2.52	17	11	3.9	95	10,20	BLK
BWLD00241715680□00	68	2.52	17	11	5.5	95	10,20	BRN
BWLD00241715101□00	100	1	12	9	9	70	5,10,20	RED


NOTE: □-tolerance J=±5% /K=±10% / M=±20%

1. Operating temperature range -40°C ~ 105°C (Including self - temperature rise)
2. L/Q Test OSC @200mV.
3. IDC for Inductance drop 10% from its value without current.

BWLD00241715 Series Specification

8 BWLD00241715 Series

8.1 Construction:



8.2 Material List:

NO	PART	MATERIAL
1	WIRE	COPPER
2	EPOXY	UV GLUE
3	CORE	FERRITE
4	TERMINAL	Ag/Ni/Sn

BWLD00241715 Series Specification

9 Reliability OF Ferrite Wire Wound Chip Inductor/FERRITE SERIES


1-1.Environmental Performance

No	Item	Specification	Test Method		
1-1-1	Temperature Cycle	Appearance: No Damage Inductance: within $\pm 10\%$ of initial value Q change: within $\pm 30\%$ of initial value	One cycle:		
			Step	Temperature ($^{\circ}\text{C}$)	Time (min)
			1	-40 ± 3	30
			2	25 ± 2	3
			3	105 ± 3	30
4	25 ± 2	3			
1-1-2	High Temperature Resistance	There should be no evidence of short or open circle	Total: 5 cycles Measured After Exposure in The Room Condition For 1hrs		
1-1-3	Low Temperature Resistance		Temperature: $105\pm 3^{\circ}\text{C}$ Time: 1000Hrs Measured After Exposure In The Room Condition For 1Hrs		
1-1-4	Humidity Load Life		Temperature: $-40\pm 3^{\circ}\text{C}$ Time: 1000Hrs Measured After Exposure In The Room Condition For 1Hrs		
			Temperature: $40\pm 2^{\circ}\text{C}$ Relative Humidity: 90~95% Load: Allowed DC Current Time: 96Hrs		

1-2.Mechanical Performance

No	Item	Specification	Test Method
1-2-1	Resistance TO Soldering Heat	Appearance: No Damage	1. The device should be reflow soldered on PCB (peak $260^{\circ}\text{C} \pm 5^{\circ}\text{C}$ for 10 seconds) 2. Solder Composition: Sn/Ag3.0/Cu0.5 3. Test time: 6 minutes
1-2-2	Solder ability	The Electrodes Shall Be At Least 95% Covered With New Solder Coating	1. Pre-Heating: 150°C , 1min. 2. Solder Composition: Sn/Ag3.0/Cu0.5 3. Solder Temperature: $245\pm 5^{\circ}\text{C}$. 4. Immersion Time: 4 ± 1 sec.
1-2-3	Component Adhesion (Push Test)	1 Lbs. For 0402 1 Lbs. For 0603 2 Lbs. For 201614 2 Lbs. For 0805 4 Lbs. For The Rest	The device should be reflow soldered ($245\pm 5^{\circ}\text{C}$ For 10 seconds) to a tinned copper substrate. A force gauge should be applied to the side of the component. The device must withstand a minimum force of 1or2or4 pounds without a failure of the termination attached to component

BWLD00241715 Series Specification



Lead-Free(LF)標準溫度分析範圍

Refer to J-STD-020C

管制項目 Item.	升溫區 Ramp-up	預熱區 Pre-heating	迴焊區 Reflow	Peak Temp	冷卻區 Cooling
溫度範圍 Temp.scope	R.T ~ 150°C	150°C ~ 200°C	Above 217°C	260±5°C	Peak Temp.~150°C
標準時間 Time spec.	-	60 ~ 180 sec	60 ~ 150 sec	20 ~ 40 sec	-
實際時間 Time result	-	75 ~ 100 sec	90 ~ 120 sec	20 ~ 35 sec	-

NOTE:


- 1.Re-flow possible times : within 3 times
- 2.Nitrogen adopted is recommends while in re-flow
- 3.Products can only be soldered with reflow

BWLD00241715 Series Specification

10 Packaging:

10.1 Packaging -Cover Tape


The force for tearing off cover tape is 10 to 100 grams in the arrow direction.



10.2 Packaging Quantity

TYPE	PCS/REEL
241715	2000

10.3 Reel Dimensions




Dimensions in mm

TYPE	A	B	C	D
241715	178±1	60±0.5	12±0.5	1.5±0.5

BWLD00241715 Series Specification


10 Packaging:

10.4 Tape Dimensions in mm



TYPE	A	B	D	E	F	H	I	P	P0	P2
241715	8	1.60	2.4	3.5	1.75	1.45	0.22	4	4	2

11 Recommended Land Pattern:



Dimensions in mm









TYPE	H(In/mm)	I(In/mm)	J(In/mm)
241715	0.07/1.78	0.04/1.02	0.037/0.95

12 Note:

- Please make sure that your product has been evaluated and confirmed against your specifications when our product is mounted to your product.
- Do not knock nor drop.
- All the items and parameters in this product specification have been prescribed on the premise that our product is used for the purpose, under the condition and in the environment agreed upon between you and us. You are requested not to use our product deviating from such agreement.
- The storage period is less than 12 months. Be sure to follow the storage conditions (Temperature: 5 to 40°C, Humidity: 10 to 75% RH or less).
If the storage period elapses, the soldering of the terminal electrodes may deteriorate.
- Do not use or store in locations where there are conditions such as gas corrosion (salt, acid, alkali, etc.).
- The moisture sensitivity level (MSL) of products is classified as level 1.

BWLD00241715 Series Specification

13 Graph:



BWLD00241715 Series Specification

